## FASTER THAN VISION

## The FASTEC HS7

Full high-definition (1920 x 1080) @ 2500fps, the HS7 captures detailed scenes for breathtaking slow-motion playback.

Use lower resolutions for technical work at much higher frame rates.

High-Speed Video Capture!
High-Speed Image Storage!
High-Speed Image Transport!
High-Speed Application Workflow!





- Advanced architecture for enhanced workflow
- Camera with optical interface affords high-bandwidth transport using industry-standard fiber cabling
- Extensible Linux Camera Controller, compatible with standard displays and input devices, including Bluetooth and WiFi
- Run your own applications on the camera controller
- Attach high-speed high-capacity mass storage via USB3.1 Gen2 or Thunderbolt 3 interfaces

## **HS7 Specifications**

•					
Sensor	10-bit 1920 x 1080 CMOS with 10μm pixels				
Minimum Exposure	1 microsecond				
Light Sensitivity	ISO 4800 (mono)				
Interconnect	12 Channel Type B Fiber Optic patch cable with MPO connectors				
Calibration Shutter	Built-in mechanical shutter for black-level calibration				
Image Memory	8GB, 16GB, or 32GB (in camera)				
Mass Storage	Up to 2TB NVMe SSD (in camera)*				
File Formats	Stacks – BMP, DNG (color), JPEG, TIFF (processed or raw) Video – AVI, CAP (raw), MP4				
Lens Mount	Micro Four Thirds (MFT) Standard; C, F, EF, PL, and more via adapters				
Lens Control	Software control: Focus, Aperture, Zoom				
Control Software	FasMotion native on Controller, with network support: FasMotion (Windows/MacOS/Linux application) on networked PC				
Marker & Metadata	Image window playback time line, Fas <i>M</i> otion o-scope mode, XML file				
External I/O Ports	3 configurable ports: Trigger In/Out, Sync In/Out, Arm In/Out, or General Purpose In @ 3.3v LVTTL, or 5v TTL, or switch closure				
Construction	Anodized machined aluminum housing				
Power	Camera: 12v 30w; Controller 19v 90w				
Environment	+5°C to +40°C				
Size and Weight	and Weight 114mm (4.5") W x 114mm (4.5") H x 76mm (3") D. 1 Kg (2.2 lbs.)				

## **Example Record Rates and Times**

	Resolution	Max Frame Rate 8 or 10 bits (Normal mode)	Record Time 8 bits to 32GB memory	Max Frame Rate 8 bits (Streaming to SSD)	Record Time 8 bits streaming to 1TB SSD*
	1920 x 1080 (HD: 1080p)	2500 fps	6.6 sec	723 fps	11.2 min
	1280 x 1024 (SXGA)	2634 fps	9.8 sec	1144 fps	11.2 min
	1280 x 720 (HD: 720p)	3726fps	9.8 sec	1627 fps	11.2 min
	1024 x 768 (XGA)	3497 fps	12.4 SeC	1907 fps	11.2 min
	800 x 600 (SVGA)	4455 fps	16 sec	3124 fps	11.2 min
	800 x 450	5921 fps	16 sec	4184 fps	11.2 min
	640 X 480 (VGA)	5537 fps	20.1 SeC	4881 fps	11.2 min
_	512 X 384	6874fps	25.2 sec	5000 fps	17.3 min
_	512 x 256	10.136 fps	25.8 sec	5000 fps	26 min
_	412 X 212	12.000 fps	32.6 sec	5000 fps	39 min
	220 x 64	35,168 fps**	51.3 sec	5000 fps	2 hours

*NOTE:* Frame rates increase with a decrease in vertical resolution only. All frame rates shown may be achieved at full horizontal resolution (1920).

\*Streaming mode with "D" option only.

All Specifications subject to change.

17150 Via Del Campo, Ste. 301 San Diego, CA 92127 USA 1.858.592.2342

<sup>\*\*</sup> Maximum frame rate